



Elsanek Ref. **CARDIGAN Olefine**

UNIFORMTECH

QUIROTECH

olefine
TECHNOLOGY

Azul/Blue **2727CP**

Verde/Green **7726CP**

Azul/Blue **2717CP**

Gris/Grey **429CP**

Blanco/White



Composición / <i>Composition</i>	98% Olefine + 2% Elastomer	
Peso / <i>Weight</i> (Grams/m ²)	60 ± 5%	UNE 40-339-76
Ligamento / <i>Ligament</i>	CANALE 1x1	
Ancho / <i>Width</i> (cm)	7.5	
Encogimiento al lavado 75°C / <i>Washing shrinkage 75°C</i>	5%	EN 6330/15797
Pilling Martindale	Nulo / <i>Null</i>	EN 12945-2

Instrucciones de lavado / *Washing instructions:*



Temperatura lavado:
recomendado a 40°C / max. 75°C
*Washing temperature:
recommended at 40°C / max. 75°C*



Permite el uso de lejía, cloro o cualquier otro detergente.
It allows the usage of bleach, chlorine or any other detergent



Secado con secadora: Temperatura recomendada: 40°C (max. 40°C). Duración: máximo 20 minutos + 5 minutos en frío (en función de la carga). / **Secado con tunel de secado:** Temperatura recomendada: 70°C (max. 70°C).

Drying using a drying machine: Recommended temperature: 40°C (max. 40°C). Duration: maximum 20 minutes + 5 minutes cold wash (depending on the load). / **Drying using tunnel:** Recommended temperature: 70°C (max. 70°C).



No planchar
Do not iron



Se recomienda plegar o colgar la pieza de ropa después del proceso de secado para reducir las arrugas.
It is recommend to fold or hang the garments after finishing the drying process in order to reduce the amount of wrinkles.